

## TECNICAL INFORMATION

### STANDARD UNE/EN 14411:2016

DRY PRESSED CERAMIC TILES WITH WATER ABSORPTION HIGHER THAN 10%

Wall Tile

Reference: **GUBI LIGHT, CLOUD, TAUPE, ANTHRACITE (DUCTILE)**

Format: 898x2698 mm

Thickness: 6 mm

| Standard            | Features                                                                                                                                            | Required Value                                                          | Value                         |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|-------------------------------|
| Normativas          | Características                                                                                                                                     | Valores Requeridos                                                      | Valor                         |
| EN-ISO 10545 / 3    | Water absorption / Absorción de agua                                                                                                                | Grupo BIII / E > 10 %                                                   | E > 10 %                      |
| EN-ISO 10545 / 4    | Breaking strength / Resistencia a rotura                                                                                                            | > 200 N                                                                 | > 400 N                       |
| EN-ISO 10545 / 4    | Bending strength / Resistencia a la flexión                                                                                                         | > 12 N/mm <sup>2</sup>                                                  | > 20 N/mm <sup>2</sup>        |
| EN-ISO 10545 / 11   | Crazing resistance / Resistencia al cuarteo                                                                                                         | Required / Exigida                                                      | Complies with / Cumple        |
| EN-ISO 10545 / 13   | Chemical resistance: acids and alkalis / Resistencia química: ácidos y álcalis                                                                      | Indicated by the manufacturer / Indicado por el fabricante              | GLA<br>Complies with / Cumple |
| EN-ISO 10545 / 13   | Chemical resistance: domestic cleaning products and swimming pool salts / Resistencia química: productos de limpieza doméstica y sales para piscina | Min. GB                                                                 | GA                            |
| EN-ISO 10545 / 14   | Stain resistance / Resistencia a las manchas                                                                                                        | Min. Clase 3                                                            | Clase 5                       |
| EN-ISO 10545 / 2    | Surface quality / Calidad de la superficie                                                                                                          | Min. 95% of tiles without defect / Min. 95% de los azulejos sin defecto | Guaranteed / Garantizado      |
| UNE EN 13501-1:2002 | Fire Reaction Test / Test reacción al fuego                                                                                                         |                                                                         | A1 / A1FL                     |
| VOC                 | Do not release volatile elements / No desprende elementos volátiles                                                                                 |                                                                         |                               |

## QUALITY DEPARTMENT LIVING CERAMICS

STANDARD INTERNATIONAL ISO 9001  
QUALITY MANAGEMENT INTERNATIONAL STANDARD OBTAINED IN 2015.



GREEN BUILDING COUNCIL MEMBERSHIP

